NABCO ENTRANCES TECHNICAL BULLETIN

S82 W18717 Gemini Drive Muskego, WI, 53150 Phone: (877) 622-2694, Fax: (888) 679-3319 www.NabcoEntrances.com Date: 4/18/14

Who is the technical contact? Chad Schumacher

NEW GT1175 SLIDING DOOR HURRICANE PACKAGE Dade County NOA Approved

Nabco Entrances is now offering a new GT1175 Sliding Door Hurricane System with lots of upgrades to allow larger sizes and to withstand higher pressures. New features have also been added. Both the new and older model hurricane packages will continue to be offered. The new model H105 has some differences from the existing model H60. These are:

- Stronger carrier, pivot, and bottom guide components
- Pressure ratings up to 105psf, highest in the industry. Additional size/pressure info below
- Larger sizes
- AHCA Approved Panic Hardware for secure locking during a hurricane
- · Heavy duty interlocks are used in place of flush bolts for one-motion emergency egress
- Muntin bars are now available
- New dry-glazing system allows for glass to be replaced without replacing the whole panel
- Pocketed jambs allow jamb anchors to be hidden and require fewer anchors

	Existing Hurricane Package - Model H60	New Hurricane Package - Model H105				
Max Height:	7 ft. 8 in.	8 ft. 8 in. Additional size/pressure info below				
Max Width:	16 ft.	18 ft. Additional size/pressure info below				
Glass:	Impact: 1/2" Solutia Saflex (Wet Glaze) Non-Impact: 5/16" Tempered (Dry Glaze)	Impact: 7/16" Dupont Sentry Glass (Dry or Wet Glaze) Non-Impact: 1/4" Tempered (Dry Glaze)				
Lock Options:	Standard single - 3 point Standard bipart - 3 point active panel Flush bolt inactive panel 4550 handles are optional	Single - 2 Point or 3 Point (w/Indicators on interior) 4550 handles are optional Bipart - 3 Point on active panel/2-Point on other panel Or, 2 point on both panels (w/Indicators on interior) 4550 handles are optional Adams Rite G86 Panic Device Exterior Key cylinder standard				
Flush bolts:	Required	Applicable on Full Open w/ Muntin Only Not Used				
Stiles:	Narrow or Medium	Medium Only				
Bottom Rail:	4", 6.5", or 10"	6.5" or 10"				
Muntin:	None	4" or none				
Agency Approvals:	Nat. Accreditation & Management Institute, Inc. (NAMI) Florida Product Approval (FPA)	Miami-Dade (NOA) Florida Product Approval (FPA)				

New Hurricane Package (Size vs. Pressure)

UNIT HEIGHT (inches)	104	93	86	80	75	70				Pressure rating	
	100	97	90	83	78	73	70		_	(PSF)	
	96	101	93	87	81	76	74	70		_	
	92	105	97	90	84	79	77	74	70		
		144	156	168	180	192	196	204	216	←←Bi-Part	
		72	78	84	90	96	98	102	108	$\leftarrow \leftarrow$ Single	
		UNIT WIDTH (inches)									
										Bull	etin Number: 6