NABCO Entrances - Swing Door System - Shop Drawing Request

			Distributor #:	Door #:	
Date:			Job Name:		
			Contact:		
			Qty Required:		
lotes:					
1. Iype of Header: Bottom Load Side Load			8. Application: Single Simultaneous Pair		
	400 C *	8400 C *			
	_ 400 C	8300 F	9. Finish:		
	_300 F *	8400 F *	Clear (204)	Dark bronze (313)	
		01001			
	* Electrical Access		10. Adds:		
		Hole in Top of Header?	10" Bottom rail		
	* Access Hole for Cam Adjustment in Top		Acuvision on swing side		
	of Header?		Additional auminum cart bars <i>(ea)</i>		
	No Holes Required		Transom (up to 120")		
=" _ with a	enter pivot and fingerg	nuard	Vertical in transon	n	
	Continuous Hinge	juaru			
			11. Changes & Deducts:		
2. Swing & Handing:			Deduct Guide rails		
Inswing with panic breakout			Acusensor in lieu of Optex Reaction Two		
	Inswing without panic breakout (check codes)		Deduct one Aluminum Cart Bar		
	Outswing		Deduct Finger Gu		
	(Place Back to Pivot		Deduct Jamb Tub	es	
	_RT Hand IN	RT Hand OUT	Deduct Muntin		
	LT Hand IN	LT Hand OUT	Deduct MS Lock		
3. Glass Thickness:		Deduct Push Bar and Handle Key switch in lieu of rocker switch			
Door Glass Thickness (1/4", 1", other)				OF TOCKET SWITCH	
	Transom Glass Thickness (1/4", 1", other)		12. Profile:		
	(glass not included)		Narrow Stile (standard profile)		
	, , , , , , , , , , , , , , , , , , , ,		Medium Stile	. ,	
. Frame D	imensions:				
	Header Height (to to		13. Swing Door Size:		
	(90" standard for bot	-	Width	Narrow Stile (2-1/8"	
	(91" standard for side		Height	Medium Stile (4")	
	_Height Including Trai			t (standard 42-1/4" to top)	
	-	" standard width)	Muntin Size	2" Standard	
	Frame Width			Other Size (Special)	
. Pivot typ	be:		14. Door Panel Accessories:		
	Ctr Pivot	with FG	Push Bar Both Sid	des	
	_	no FG	(in lieu of standard	d Push Bar & Pull Handle)	
	Continuous Hinge		Prep in Field (har	dware shipped loose)	
			15 Door Divot Loostion		
lamh Tu	ihas			15. Door Pivot Location:	
. Jamb Tu		tord)			
5. Jamb Tu	ibes _1-3/4" x 4-1/2" <i>(stand</i> _4.5" x 4.5" jambs (20	-	Outer Jambs Center Post (send	d skatch)	

