

# NABCO Entrances - GT1500 Convenience Window - Shop Drawing Request

Company: \_\_\_\_\_

Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_

Date: \_\_\_\_\_  
 \_\_\_\_\_

Job Name: \_\_\_\_\_

Contact: \_\_\_\_\_

**Notes:**

**Type of Unit:** GT1500 - \_\_\_\_\_ (architectural drawing #)

\_\_\_\_\_ Quantity

**Mode:**

\_\_\_\_\_ Bi-part

\_\_\_\_\_ Automatic

\_\_\_\_\_ Single

\_\_\_\_\_ Manual

**Hand of Unit:**

\_\_\_\_\_ Right hand *viewed from exterior*

\_\_\_\_\_ Left hand

**Additions:**

\_\_\_\_\_ Holding Beam/s  
 Qty: \_\_\_\_\_

**Frame Size:**

\_\_\_\_\_ Width (min. 30" singles - 42" Bi-parts)  
 \_\_\_\_\_ Header Height without Transom (std. = 35-3/4") (min. 30")  
 \_\_\_\_\_ Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom

\_\_\_\_\_ Armored Strike  
 \_\_\_\_\_ "D" Handle in lieu of Recessed  
 on Interior Panels (P/N 21-3754)  
 \_\_\_\_\_ "4570" Handle in lieu of Recessed  
 on Interior Panels (P/N P/N 14-10588)

**Sliding/Fixed Panel**

**Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"

**Transom Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"

**Finish:**

\_\_\_\_\_ Clear (204)  
 \_\_\_\_\_ Dk bronze (313)  
 \_\_\_\_\_ Special anodize \_\_\_\_\_  
 \_\_\_\_\_ Paint/Clad \_\_\_\_\_  
 \_\_\_\_\_ Prep for paint by distributor