Bulletin Technica

NABCO ENTRANCES TECHNICAL BULLETIN

Date: 8/17/16

S82 W18717 Gemini Drive Muskego, WI, 53150 Phone: (877) 622-2694, Fax: (888) 679-3319 www.NabcoEntrances.com

Who is the contact? Technical Support Department

Introduction to the Acusensor M



Special features:

- Increased range and adjustability
- Active infrared for approach and presence
- Able to look back through the threshold
- Multi-color LED to show sensor's status
- Monitoring function to comply with upcoming ANSI A156.10 standard
- Suitable for sliding, swinging, and folding doors
- Detection depth can be increased with an angled spacer, P/N V-00742 (sold separately)
- Accommodates new installations or sensor upgrades
- All features comply with existing and upcoming ANSI A156.10 standard

Acusensor M is currently available and will start shipping with GT1175 and GT1400 packages soon.		Threshold protection	Monitoring function	Detection area at height of 87"
Sensor package (without spacer): A-01306 (includes sensor, black cover, modified harness) Sensor Only (with black cover): V-00741 Replacement cover (black): V-00744 Replacement cover (silver): V-00743 Harness only: A-01292 Angled Spacer: V-00742	Acusensor M	Yes	Yes	114" W 72" D (without spacer) 78" D (with spacer)
	Acusensor 3	No	No	95.7" W 54.7" D
	Acuzone	Yes	No	109" W (presence only) 97" D (with microwave)

